

Fire Dome Ceiling Mount Speaker FCVS4F

Overview

The FCVS-4F Ceiling Mount Speaker features an iron-made dome that prevents the fire from spreading in the ceiling in case of an emergency situation. The speaker can be easily installed using the speaker mounting spring, and the dome can also be easily mounted in the speaker mounting hole in the ceiling panel. The FCVS4F certificated European Standard EN 54-24 and complies with the British Standard BS 5839-8.



Specifications

Rated Noise Power	6 W (100 V Line), 3 W (70 V Line)
Rated Impedance	100 V line: 1.7 kΩ (6 W), 3.3 kΩ (3 W), 6.7 kΩ (1.5 W), 13 kΩ (0.8 W) 70 V line: 1.7 kΩ (3 W), 3.3 kΩ (1.5 W), 6.7 kΩ (0.8 W), 13 kΩ (0.4 W)
Sensitivity	90 dB (1 W, 1 m) (500 Hz - 5 kHz, pink noise) 79 dB (1 W, 4 m) (100 Hz - 10 kHz, pink noise) according to EN 54-24 91 dB (1 W, 1 m) (100 Hz - 10 kHz, pink noise) converted based on EN 54-24
Maximum Sound Pressure Level	85 dB (6 W, 4 m) (100 Hz - 10 kHz, pink noise) according to EN 54-24 97 dB (6 W, 1 m) (100 Hz - 10 kHz, pink noise) converted based on EN 54-24
Frequency Response	160 Hz - 13 kHz
Coverage Angle(-6dB)	500 Hz: 186 °, 1 kHz: 178 °, 2 kHz: 148 °, 4 kHz: 76 °, according to EN 54-24
Environmental Type	A (indoor applications) according to EN 54-24
Speaker Component	12 cm (5) cone-type"
Dimensions for Fixing Hole	±3 ±0.12" φ156 (mounting hole) × 30 (maximum ceiling thickness) mm (φ6.14 × 1.18)"
Speaker Mounting Method	Spring catch
Applicable Cable	Solid wire: φ1.0 - φ3.0 mm (AWG18-9)
Connection	Screw connector (steatite terminal) bridging
Finish	Baffle: Aluminum, off-white (RAL 9010 or equivalent color), paint Grille: Aluminum net, off-white (RAL 9010 or equivalent color), paint Dome mounting bracket: Steel plate, trivalent chromate treatment plating Fire dome: Steel plate, black, painting
Dimensions	φ180 × 11 (exposed section) + 110 (D) mm (φ7.09 × 0.43" + 4.33")"
Weight	1.4 kg (3.09 lb) (bracket, fire dome included)
Accessory	Rubber grommet ...2, Paper pattern ...1

ADEVA LTD. Fire Alarm Systems

Guldeste Sok. No:24 Yakacik
Kartal / Istanbul / Turkey

Tel: +90 (0)216 5982800 Fax: +90 (0)216 5982899
Email: info@adevafire.com www.adevafire.com

Copyright © 2009 ADEVA. All rights reserved.

All technical data is correct at time of publication and is subject to change without notice. All trademarks acknowledged. Installation information: in order to ensure full functionality, refer to the installation instructions as supplied.